



130 BBL ASME DOT 407/412

PROVEN DESIGN

DRIVER FRIENDLY

DOT 407/412

A.S.M.E.

BUILT READY FOR WORK

"Ride With Anality"



800.864.4887

SPECIFICATIONS

SHELL: 60" I.D.X36'X1/4" STRAIGHT CYLINDER, SA-36 MILD STEEL.

HEADS: 60" O.D.X1/4" FLANGED AND DISHED, SA-36 MILD STEEL.

BAFFLES: Two 1/4" flared and dished surge style baffles.

STIFFENING RINGS: SEVEN 3/8"X21/2" FLAT BAR TYPE.

MANWAYS: THREE 20" HINGED TYPE MANWAY WITH SIX GREASEABLE WING NUT STYLE LATCHES.

VACUUM KITS: ONE 12" DUTSIDE SCRUBBER WITH 6" STAINLESS STEEL FLOAT BALL. 30/60 VACUUM/PRESSURE

GAUGE ON REAR HEAD. INSIDE PORTAL SHUTOFF IN 20" MANWAY WITH STAINLESS FLOAT BALL AND BUNA SEAT.

PLUMBING: Two 4" outlets with 4" wafer style butterfly valves with buna seats; one 4" and one 3"

ALUMINUM QUICK CONNECT C/W DUST CAP, 2" RELIEF VALVE, AND 2" BLOW DOWN LINE.

FENDERS: COMBINATION HOSE RACK AND FENDERS, SLEEK PROCO FENDERS KEEPS HOSES TOWARD TANK.

DRAINS IN FENDERS HAVE 1" CONNECTION FOR BALL VALVE.

LEVEL GAUGE: STAINLESS STEEL FLOAT BALL LEVEL INDICATOR MOUNTED IN CENTER OF REAR HEAD.

BUMPER: COMBINATION REAR STEP USING 8"X4" HEAVY BOX TUBING BUMPER C/W LIGHT GUARDS.

LIGHTS: 12 VOLT LED LIGHT SYSTEM TO COMPLY TO FEDERAL SAFETY STANDARDS #108. LED GROTE LIGHTS IN

"Ultra-Blue Seal" harness system. Double halogen work light, strobe light.

TOOL BOX: HEAVY DUTY 18"X18"X36" WITH LOCKABLE SEALED DOOR MOUNTED ON DRIVER SIDE.

LANDING GEAR: TWO SPEED CRANK UP STYLE WITH SANDSHOES.

FRAME: 1/4" FORMED FULL LENGTH L-TYPE FRAME.

SUSPENSION/AXLES: OPTIONS: SINGLE POINT, 4 SPRING HUTCH 9700, AIR RIDE

25,000# CAPACITY AXLES, STEMCO SEALS, AUTOMATIC SLACK ADJUSTERS, OUTBOARD DRUMS, ABS BRAKES

TIRES: STEEL BELTED RADIALS 11R24.5 TIRES. 10 HOLE HUB PILOT STEELS WHEELS

PAINT: SANDBLAST, PRIME, AND PAINT ONE COLOR (CUSTOMERS CHOICE) USING URETHANE PAINT.

LINER: SANDBLAST INSIDE OF TANK AND APPLY TNEMEC 391 ACID LINER, OR FRP.

CATWALK: 12" WIDE X 36" LONG GALVANIZED WALKWAY SQUARE TUBING HANDRAILS RUNNING FULL LENGTH WITH

CENTER LADDER. WALKWAY WILL BE MOUNTED AT 9 0'CLOCK DRIVER'S SIDE.

Proco will customize to your specifications.

